



JUNCKERS STRONG LACQUER

FOR RESIDENTIAL AND
LIGHT COMMERCIAL USE

JUNCKERS STRONG

Junckers Strong is an NMP-free, one - component water based polyurethane lacquer which is suited for residential and light commercial use. The new, NMP free version does not yellow, and provides an extremely light, natural appearance to all hardwood and softwood floors.

The product is used on both previously finished as well as on new or sanded old floors, and is also suitable for lacquering all kinds of indoor woodwork. It benefits from excellent flow, defoaming and leveling making the product extremely easy to use.

TECHNICAL DATA

Product:

Water-based polyurethane lacquer.

Package sizes:

2.5 litre, 5 litre and 10 litre.

Appearance:

Creamy/milky in the container. Colourless film when dry. Sanded floors will appear with a lighter colour immediately after finishing but as time passes the wood colour will change, although water-based finishes always will give rise to a lighter appearance than solvent-based finishes.

Gloss:

Matt, Silk or Gloss.

Coverage:

10 m² per litre.

Application tools:

Brush, short hair mohair roller, air/airless spray.

Substrate temperature:

Minimum 10°C.

Dilution:

Delivered ready for use. Dilution is not recommended.

Drying time:

Approx. 4 hours at 20°C and 50 %RH.
Important! Apply only 2 coats per day.
Maximum hardness is achieved after 3 days.



Junckers Ltd.

Unit a, 1 Wheaton Road, Witham,
Essex CM8 3UJ.
General Enquiries United Kingdom.
Tel: 01376 534 700.
Brochures tel: 01376 534 700.
E-mail: brochure@junckers.co.uk.
Sales tel. 01376 534 710.
E-mail: sales@junckers.co.uk
Fax: 01376 514 401.
Technical tel. 01376 534 720.
E-mail: tech@junckers.co.uk
Fax: 01376 534 735.
website www.junckers.co.uk